

EnviroSmart Loose Fill

STANDARD

ATTIC CARD

30 LB BAG

Insulation to be applied at these initially installed thicknesses and maximum coverages to provide the levels of thermal resistance (R) shown.

Desired R-Value	Initially Installed Thickness (approx inches)	Settled Installed Thickness (approx inches)	Maximum Ft ² Per Bag		Minimum Bags Per 1000 Ft ²		Minimum Weight (lbs/sq ft)
			No Adj'm't For Framing (Sq Ft)	2x6 Joists 16" O.C. (Sq Ft)	No Adj'm't For Framing (# Bags)	2x6 Joists 16" O.C. (# Bags)	
ATTIC							
11	3.30	3.00	87.7	97.2	11.4	10.3	0.342
13	3.90	3.50	73.2	81.1	13.7	12.3	0.410
19	5.70	5.10	49.0	54.1	20.4	18.5	0.612
20	6.00	5.40	44.7	49.1	22.4	20.4	0.671
22	6.60	5.90	40.1	43.7	24.9	22.9	0.748
24	7.20	6.50	36.3	39.3	27.6	25.5	0.827
30	9.00	8.10	27.2	29.0	36.7	34.4	1.101
32	9.60	8.60	25.1	26.6	39.9	37.6	1.196
38	11.40	10.30	21.0	22.1	47.6	45.3	1.429
40	12.00	10.80	19.5	20.4	51.4	48.9	1.541
44	13.20	11.90	17.5	18.3	57.1	54.7	1.714
48	14.40	13.00	15.9	16.5	63.1	60.6	1.892
50	15.00	13.50	15.1	15.6	66.4	63.9	1.993
60	18.00	16.20	12.1	12.5	82.4	79.8	2.473
SIDE WALLS							
13 (2x4)	3.50	3.50	25.7	28.5	38.9	35.1	1.167
20 (2x6)	5.50	5.50	16.4	18.1	61.1	55.2	1.833

Note: Coverage figures based on professional contractor installing product, insulating attic without water, insulating walls by dry-blowing wall cavities through holes cut in wall board. EnviroSmart loose-fill is not designed to be wet-sprayed into wall cavities.

STATEMENT OF COMPLIANCE

JOB ADDRESS: _____

This is to certify that the insulation has been installed in accordance with the above chart to provide and R-value of _____ using _____ bags of insulation to cover _____ net sq. ft.

Installer Name

Date



P.O. Box 40970 Houston TX 77240 * 713-937-0900 * tasconindustries.com

7/25/2009